

FD70D

SPECIFICATIONS	Item		FD50T	FD60T	FD70T	FD80T	FD100T
	Load capacity	kg	5000	6000	7000	8000	10000
	Load center	mm	600	600	600	600	600
DIMENSIONS	Max. lifting height(VM300)	mm	3000	3000	3000	3000	3000
	Turning radius (outside)	mm	3250	3300	3360	3550	3900
	Total length (without fork)	mm	3455	3530	3590	3740	4255
	Overall width	mm	1995	1995	1995	1995	2245
	Mast height(fork lowered)	mm	2500	2500	2500	2625	2850
	Height to head guard	mm	2450	2450	2450	2450	2560
	Fork size(L×W×T)	mm	1220×150×60	1220×150×60	1220×150×65	1220×170×75	1220×175×75
	Tilt range(forward/backward)	deg	6/12	6/12	6/12	6/12	6/12
	Truck weight	kg	8050	8750	9450	10450	12450
TIRES	Size-front		8.25×15-14PR	8.25×15-14PR	8.25×15-14PR	8.25×15-14PR	9.00×20-14PR
	Size-rear		8.25×15-14PR	8.25×15-14PR	8.25×15-14PR	8.25×15-14PR	9.00×20-14PR
ENGINE	Model		Mitsubishi S6S-T	Mitsubishi S6S-T	Mitsubishi S6S-T	ISUZU 6BG1	ISUZU 6BG1
	Rated power	kw/rpm	67.6/2300	67.6/2300	67.6/2300	82.3/2000	82.3/2000
	Rated torque	Nm/rpm	293/1700	293/1700	293/1700	418/1500	418/1500
	Number of cylinder		6	6	6	6	6
	Displacement	L	4.996	4.996	4.996	6.494	6.494

